



The JNR 90L Beam is made of a new type of high temperature strength of engineering plastics and cast aluminum casing with nice outlook. It adopts a 90W white LED lamp which features high brightness and stability. And it's available independently controlled and linkable with each other for operation. JNR 90L Beam is applicable for large-scale live performances, theater, studio, nightclubs and discos.



**JNR 90L BEAM**

■ JNR-8124


**Specification**

- Input Voltage: AC 90-260V 50/60Hz
- LED Quantities: 1\*90W white LED
- Control Signal: DMX512, master-slave and sound activated or auto operation
- Control Channel: 10/12 DMX channels USITT DMX-512
- Power Consumption: 135W
- Net Weight: 5.8kg

DMX | CE | LED | 0.2m | IP20 | Tc150°C | Ta40°C | X


**Detail**

- A 90W white LED lamp
- 50,000 hours lifespan and low power consumption
- 8/16 bit smooth and precise resolution for PAN/TILT movement
- 360°/540°/630° PAN and 90°/180°/270° TILT movement
- Scan position memory, auto reposition after unexpected movement
- Specific optic system with 2° projection angle
- Improved optics and flat beam field
- 1 static gobo wheel with 17 gobos plus open
- 1 color wheel with 14 colors plus open
- Variable direction rainbow effect with speed adjustable
- 8-facet prism with variable speed and direction
- 0-100% linear LED dimmer
- 25T/sec high speed LED shutter/strobe effect with variable speed
- Preset variable/random strobe and dimming pulse effect
- 10/12 DMX channels USITT DMX-512
- DMX512, master-slave, and sound activated controllable or auto operation (7 built-in programs)
- DMX recorder and edit function integrated
- Red background LED display
- Powercon connector IN/OUT
- 3-pin XLR connectors IN/OUT
- Fan cooling system
- Constant temperature readout and management function
- 45°C max ambient temperature
- IP20 protection rating
- 55dB at 3'dB rating
- 1\*hanging kit



5.8KG

**Light Output (FC=LUX × 0.0929)**



**Static Gobos**



**Colors**

